

PURCHASER	P.O. #	DATE
PROJECT	LOCATION	
ENGINEER	ARCHITECT	
SUBMITTED BY	FOR APPROVAL	FOR REFERENCE

ITEM	PLAN DESIGNATION	QUANTITY	COOLING BTU/H	VOLTAGE	FRIEDRICH MODEL

Why Precision Inverter® Technology matters

Every Chill® Premier Inverter Room Air Conditioner is equipped with a Precision Inverter® compressor, which provides:

Variable Comfort Technology

- Precision Inverter® compressor operates at the precise capacity needed
- Turbo Cool boosts cooling operation by up to 41%²

Library Quiet™ Operation

- As low as 42 dB in cooling mode / 32dB in fan-only
- Soft-Start™ technology eliminates hard stop-and-starts and run at lower sound levels than other compressor types
- QuietMaster™ technology combines heavy duty insulation, stiffened sheet metal, optimized air flow and counterweights to dampen vibration
- Quiet mode operates at ultra-low fan speed for the quietest cooling available³

Smart Design

Traditional window units don't allow the homeowner to open the windows once installed, limiting the amount of fresh air, but the Friedrich Chill® Premier Inverter features a flexible design that includes:

SimpleSill™ Design – Allows the window to be opened and closed after installation
 Three-step Installation – Simplifies the process with a one-piece frame, included hardware and expandable side panels that lock the unit in place

Ultimate Efficiency

- Operates up to 35% more efficiently¹ than traditional window air conditioners
- ENERGY STAR® certified and uses sustainable R-32 refrigerant to help protect our planet

Smart Features

Designed with intelligent features that put the homeowner in control, the Chill® Premier Inverter includes industry-leading advantages like:

- Built-in Wi-Fi Control – Manage comfort from anywhere with the FriedrichGo™ App⁴
- Auto Air Sweep – Moves louvers up and down, extending the air flow for maximum circulation and cooling
- Intelligent Sleep Mode – Smart temperature auto adjustment with Turbo Fast Cooling

Smart Investment

- Every unit maintains precise temperature control while providing homeowners peace of mind through:
- Money Saver® Mode – Runs fan only when cooling to save on bills
- Clean Filter Reminder – Allows homeowners to breathe easy with washable design and automatic reminder when it's time to clean the filter
- Corrosion Resistant Coils – Extend the life of the unit, especially in coastal and harsh environments



Model Information



WINDOW INSTALLATION ONLY

CCV08, CCV10, CCV12



WINDOW OR THROUGH-THE-WALL INSTALLATION

CCV15, CCV18, CCV24

SPECIFICATIONS

Model	UPC	Cooling Btu	Volts Rated	Cooling Amps	Cooling Watts	CEER	Estimated Yearly Energy Cost	Moisture Removal-Pints/HR	Refrigerant	CFM	Wt. Net/Ship Lbs.
FIXED CHASSIS, COOL ONLY, WINDOW INSTALLATION ONLY											
★ CCV08A10A	724587442316	8,000	115	8.3	740	15.0	\$60	2.1	R-32	194	56/60
★ CCV10A10A	724587442328	10,000	115	8.3	950	15.0	\$75	3.2	R-32	253	58/61
★ CCV12A10A	724587442335	12,000	115	10.5	1,180	15.0	\$90	3.7	R-32	265	58/62
SLIDEOUT CHASSIS, COOL ONLY, WINDOW OR THRU-WALL INSTALLATION											
★ CCV15A10A	724587445749	15,000	115	13	1,600	14.4	\$110	3.8	R-32	447	85/99
★ CCV18A30A	724587445756	18,000	208/230	8.9	2,000	14.4	\$160	5.5	R-32	447	88/103
★ CCV24A30A	724587445763	24,000	208/230	14.0	2,990	12.7	\$200	6.97	R-32	458	93/107

★ENERGY STAR® models

WINDOW OR THROUGH-THE-WALL

						WINDOW INSTALLATION		THROUGH-THE-WALL INSTALLATION		Carton Dimensions Inches		
						Window Width Inches		Through-the-wall Finished Hole Inches		Height	Width	Depth
Model	Height Inches	Width Inches	Depth Inches	Depth From Front to Louvers		Minimum	Maximum	Height	Width			
CCV08A10A, CCV10A10A, CCV12A10A	13 3/8	20 5/8	19 1/4	—		21 1/2	36	WINDOW INSTALLATION ONLY		14 3/4	24 1/4	20 1/2
CCV15A10A, CCV18A30A, CCV24A30A	17	25 1/2	26 3/8	—		26 1/4	41	18 1/2	26	20	30	28 3/4

¹Minimum width achieved with both side panels in place and the side curtains removed.

CIRCUIT RATING/PLUG FACE/POWER CORD

Model	Circuit Rating Breaker or T-D Fuse	Plug Face (NEMA#)	Power Cord Length (ft.)	Wall Outlet Appearance
CCV08A10A, CCV10A10A, CCV12A10A, CCV15A10A	125V – 15A	5 – 15P	5	
CCV18A30A	250V-15A	6-15P		
CCV24A30A	250V-20A	6-20P		

Power cord is located on front left side of Chill® Premier Inverter units.



These products meet a stringent set of our company's internally defined sustainability standards

¹Up to 35% energy savings based on variable-speed inverter compressor operation at 12 Hz extra-low frequency to maintain set point versus non-inverter fixed-speed. ²Dual DC fan motor reaches set point an average of 41% faster than a standard ac fan motor operating at the same speed. ³Sound levels are also dependent on proper installation of product. ⁴WiFi broadband internet connection required; Download the FriedrichGo™ App from the App Store® or Google Play®; Receipt of notifications depend on home Wi-Fi set up; Amazon, Alexa and all related logos are trademarks of Amazon.com, Inc. or its affiliates. ⁵For complete details of the limited warranties, including applicable terms and conditions, contact your local dealer or go to Friedrich.com for a copy of the product warranty certificate.



Friedrich Air Conditioning Co. | Friedrich.com

CHILL INVERTER SUBMITTAL (REV 11-14-24)

