

DEHUMIDIFIERS

35 and 50 Pint Capacities with **Built-in Drain Pump**







Dehumidifiers

Eliminate excess humidity and moisture that can damage furnishings, and can even affect your health

Comfort & Convenience

- Built-in Drain Pump actively pumps the collected water to a designated drainage point
- Top-mount digital touch controls display room temperature and relative humidity level
- Set humidity level from 30% to 90% RH
- · Low temperature operation to 41°F
- Removable condensate bucket with handle
- · Washable, slide-out filter
- 24 hr. ON/OFF timer (timer must be set for each use-no memory)
- · 2-speed fan
- · Automatic defrost cycle
- · Auto-restart
- · Built-in casters for easy mobility
- 6 ft. power cord

Energy Efficiency

- R-32 refrigerant with low Global Warming Potential
- · Fan cycles off with the compressor
- ENERGY STAR® certified and uses sustainable R-32 refrigerant to help protect our planet

Sleek, Clean Modern Design

 Non-louvered front panel has a clean, stylish appearance that doesn't accumulate unsightly dust, pet hair and other household debris.



CONVENIENCE FEATURES FOR CAREFREE OPERATION

THREE WAYS TO DRAIN CONDENSATE:



Built-in drain pump



Slide out condensate bucket *16.2 Pints Capacity



Continuous drain option *Hose not included

Dehumidifiers

Model Information

SPECIFICATIONS

Model Number	D35B1B	D50B1B		
Dehumidification Capacity¹ (Pints/24 hrs)	35	50		
ENERGY STAR®	YES	YES		
Easy Roll Casters	Yes-built in	Yes-built in		
Built-in Drain Pump	Yes	Yes		
Drain Pump Hose (Length ft)	16' 9"	16' 9"		
Control	Digital	Digital		
Power	115V/60HZ	115V/60HZ		
Current (Amps)	5.3	7.6		
Watts	370	540		
Energy Factor (EF), L/kWh²	2.0	2.0		
Indoor Sound Power (dB)	48	54		
Compressor Type	Rotary	Rotary		
Refrigerant Type / Charge Amount (Oz)	R-32 / 8.8 Oz	R-32 / 10.9 Oz		
Operating Temperature Range	41°F- 90°F	41°F- 90°F		
Bucket Capacity (Pints)	16.25 approximate	16.25 approximate		
Dimensions (WxHxD)	15" x 23 ¹ /4" x 12"			
Net/Shipping Weight	40.78/44.75	43.65/47.62		
Carton Dimensions (WxHxD)	16 1/2" x 25" x 14"			
Limited Warranty	1 year 1 year			

DEHUMIDIFIER SIZING GUIDE

Dehumidifier capacity is usually measured in pints per 24 hours and is determined by two factors:

- 1. The size of the space that needs to be dehumidified.
- 2. The conditions that exist in the space before dehumidification. Use the chart to estimate the capacity you need.

	SMALL TO MID-SIZE SPACE	MID-SIZE TO LARGE SPACE	
Room Conditions	100 - 1,000 sq. ft.	1,000 - 2,000 sq. ft.	
DAMP Area feels damp and has a musty odor only in humid weather	D35 (35 pint)		
VERY DAMP Area always feels damp & has a musty odor & may exhibit damp spots on walls & floors	D35 (35 pint)		
WET Area always feels and smells wet and the walls & floors sweat or seepage is present	D35 (35 pint)	D50 (50 pint)	
EXTREMELY WET Area has wet floors or exhibits standing water	D35 (35 pint)	D50 (50 pint)	

POWER CORD/PLUG TYPE

Model	Circuit Rating Breaker or T-D Fuse	Plug Face (NEMA)	Wall Outlet Appearance	Power Cord Length
All models	125V-15A	5-15P		6 FT.

¹The rating is expressed in pints per 24 hour period.

As an ENERGY STAR® partner, Friedrich Air Conditioning Co. has determined that the selected ENERGY STAR® models meet the ENERGY STAR® guidelines for energy efficiency.

One year limited warranty on parts and labor.

Due to continuing research in new energy-saving technology, specifications are subject to change without notice.







 $^{^2}$ Energy Factor: The energy efficiency of dehumidifiers is measured by its energy factor, in liters of water removed per kilowatt-hour (kWh) of energy consumed or L/kWh. In general, a higher energy factor means a more efficient dehumidifier.

 $For complete \ details \ of \ the \ limited \ warranties, including \ applicable \ terms \ and \ conditions, contact \ your \ local \ dealer \ or \ go \ to \ Friedrich.com \ for \ a \ copy \ of \ the \ product \ warranty \ certificate.$









