



FastPro[®]
DESIGN



FLOATING AIR[®] Select
EXCEPTIONAL VALUE LINE

SINGLE ZONE		Friedrich System		Built-in Wi-Fi	FastPro [®] DESIGN	Friedrich Indoor SKU	Johnstone SKU	Friedrich Outdoor SKU	Johnstone SKU	Cool Btu	Heat Btu	Voltage	SEER/ SEER2	Line Sizes	Low Temp Cooling	Low Temp Heating	High Temp Cooling	Line Length Min. - Max.	Max. Height Difference	Circuit Breaker	PreCharge Line Length
WALL-MOUNTED HEAT PUMPS		SELECT	FSHW091	—	—	FSHSW09A1A	B61-504	FSHSR09A1A	B61-505	9000	9500	115	18.0/17.0	1/4"-3/8"	0° F	-4° F	115° F	7' - 66'	32.8'	25A	25'
			FSHW121	—	—	FSHSW12A1A	B61-506	FSHSR12A1A	B61-507	12000	13000	115	18.0/17.5	1/4"-3/8"	0° F	-4° F	115° F	7' - 98'	49.2'	30A	25'
			FSHW183	—	—	FSHSW18A3A	B61-508	FSHSR18A3A	B61-509	18000	19800	230/208	18.0/17.0	1/4"-1/2"	0° F	-13° F	115° F	10' - 82'	65.0'	25A	25'
			FSHW243	—	—	FSHSW24A3A	B61-510	FSHSR24A3A	B61-511	24000	24000	230/208	18.0/18.0	1/4"-5/8"	0° F	-13° F	115° F	10' - 82'	65.6'	25A	25'
			FSHW363	—	—	FSHSW36A3A	B61-512	FSHSR36A3A	B61-513	36000	34600	230/208	18.0/18.0	1/4"-5/8"	0° F	-4° F	115° F	15' - 98'	32.8'	40A	25'
		PRO	FPHW091A	✓	✓	FPHSW09A1B	B62-704	FPHSR09A1A	B61-491	9000	9500	115	19.5/18.5	1/4"-3/8"	5° F	-4° F	115° F	9.8' - 50'	33'	20A	25'
			FPHW121A	✓	✓	FPHSW12A1B	B62-705	FPHSR12A1A	B61-492	12000	13000	115	22.0/21.7	1/4"-3/8"	5° F	-4° F	115° F	9.8' - 50'	33'	25A	25'
			FPHW093A	✓	✓	FPHFW09A3B	B62-699	FPHSR09A3A	B61-486	9000	9500	230/208	22.5/22.0	1/4"-3/8"	5° F	-4° F	115° F	9.8' - 50'	33'	15A	25'
			FPHW123A	✓	✓	FPHFW12A3B	B62-700	FPHSR12A3A	B61-487	12000	13000	230/208	22.0/21.0	1/4"-3/8"	5° F	-4° F	115° F	9.8' - 50'	33'	15A	25'
			FPHW183A	✓	✓	FPHFW18A3B	B62-701	FPHSR18A3A	B61-488	18000	19000	230/208	23.3/22.5	1/4"-1/2"	5° F	-4° F	115° F	9.8' - 66'	33'	20A	25'
			FPHW243A	✓	✓	FPHFW24A3B	B62-702	FPHSR24A3A	B61-489	23500	26000	230/208	21.0/20.5	3/8"-5/8"	5° F	-4° F	115° F	9.8' - 66'	33'	30A	25'
			FPHW363B	✓	—	FPHSW36A3C	B64-296	FPHSR36A3B	B64-297	35000	35000	230/208	16.4/16.5	3/8"-5/8"	5° F	-4° F	115° F	9.8' - 66'	33'	35A	25'
		PREMIER	FRHW093A	✓	✓	FRHSW09A3B	B62-712	FRHSR09A3A	B61-501	9000	10500	230/208	28.0/27.5	1/4"-3/8"	0° F	-13° F	115° F	10' - 66'	33'	15A	25'
			FRHW123A	✓	✓	FRHSW12A3B	B62-713	FRHSR12A3A	B61-503	12000	13000	230/208	25.0/24.5	1/4"-3/8"	0° F	-13° F	115° F	10' - 66'	33'	15A	25'
CASSETTE HEAT PUMPS		PRO	FPHC093A	✓	—	FPHFC09A3B	B62-707	FPHFR09A3A	B62-772	9000	10000	230/208	22.0/20.5	1/4"-3/8"	5° F	-4° F	118° F	10' - 82'	33'	15A	25'
			FPHC123A	✓	—	FPHFC12A3B	B62-708	FPHFR12A3A	B62-773	12000	12000	230/208	23.0/20.5	1/4"-3/8"	5° F	-4° F	118° F	10' - 82'	49'	20A	25'
			FPHC183A	✓	—	FPHFC18A3B	B62-709	FPHFR18A3A	B62-774	18000	19000	230/208	22.0/20.5	1/4"-1/2"	5° F	-4° F	118° F	10' - 98'	49'	20A	25'
			FPHC243A	✓	—	FPHFC24A3B	B62-710	FPHFR24A3A	B61-498	24000	24000	230/208	19.0/18.5	3/8"-5/8"	5° F	-4° F	118° F	10' - 164'	98'	35A	25'
			FPHC363A	✓	—	FPHSC36A3B	B62-771	FPHFR36A3A	B61-499	36000	36000	230/208	19.5/18.0	3/8"-3/4"	5° F	-4° F	118° F	10' - 164'	98'	45A	25'
THE INSIDER [®] DUCTED HEAT PUMPS		PRO	FPHD093	—	—	FPHFD09A3A	B61-476	FPHFR09A3A	B62-772	9000	11000	230/208	20.0/18.0	1/4"-3/8"	5° F	-4° F	118° F	10' - 82'	33'	15A	25'
			FPHD123	—	—	FPHFD12A3A	B61-477	FPHFR12A3A	B62-773	12000	12000	230/208	19.5/19.0	1/4"-3/8"	5° F	-4° F	118° F	10' - 82'	49'	20A	25'
			FPHD183	—	—	FPHFD18A3A	B61-478	FPHFR18A3A	B62-774	18000	18000	230/208	19.5/19.0	1/4"-1/2"	5° F	-4° F	118° F	10' - 98'	49'	20A	25'
			FPHD243	—	—	FPHFD24A3A	B62-769	FPHFR24A3A	B61-498	24000	24000	230/208	18.0/18.0	3/8"-5/8"	5° F	-4° F	118° F	10' - 164'	98'	35A	25'
			FPHD363	—	—	FPHSD36A3A	B62-770	FPHFR36A3A	B61-499	36000	36000	230/208	18.0/17.5	3/8"-3/4"	5° F	-4° F	118° F	10' - 164'	98'	45A	25'

MULTI ZONE		ZONES	Friedrich Outdoor SKU	Built-in Wi-Fi	FastPro [®] DESIGN	Friedrich Indoor SKU	Johnstone		Cool Btu	Heat Btu	Voltage	SEER	Line Sizes	Low Temp Cooling	Low Temp Heating	High Temp Cooling	Line Length Min - Max	Max Height Difference	Circuit Breaker	PreCharge Line Length
OUTDOOR UNITS	2 Zones Only	FPHMR18A3A	NA	NA	NA	NA	NA	B62-711	18000	18000	230/208	SEE AHRI DATA IN BROCHURE	1/4"-3/8"	14° F	-13° F	115° F	SEE BROCHURE	49"	30A	50'
	2/3 Zones	FPHMR24A3A	NA	NA	NA	NA	NA	B61-493	24000	24000	230/208		1/4"-3/8"	14° F	-13° F	115° F		49"	30A	75'
	2/3/4 Zones	FPHMR36A3A	NA	NA	NA	NA	NA	B61-494	32000	36000	230/208		1/4"-3/8"	14° F	-13° F	115° F		49"	50A	100'
	3/4/5 Zones	FPHMR42A3A	NA	NA	NA	NA	NA	B64-283	42000	42000	230/208		1/4"-3/8"	14° F	4° F	115° F		49"	50A	125'
WALL-MOUNTED HEAT PUMPS			✓	✓	FPHMW07A3B	B62-706			7000	8500	230/208	SEE AHRI DATA IN BROCHURE	1/4"-3/8"				SEE BROCHURE			
			✓	✓	FPHFW09A3B	B62-699			9000	9500	230/208		1/4"-3/8"							
			✓	✓	FPHFW12A3B	B62-700			12000	13000	230/208		1/4"-3/8"							
			✓	✓	FPHFW18A3B	B62-701			18000	19000	230/208		1/4"-1/2"							
			✓	✓	FPHFW24A3B	B62-702			24000	24200	230/208		3/8"-5/8"							
CASSETTE HEAT PUMPS			✓	—	FPHFC09A3B	B62-707			9000	10200	230/208	SEE AHRI DATA IN BROCHURE	1/4"-3/8"				SEE BROCHURE			
			✓	—	FPHFC12A3B	B62-708			12000	13500	230/208		1/4"-3/8"							
			✓	—	FPHFC18A3B	B62-709			18000	20400	230/208		1/4"-1/2"							
			✓	—	FPHFC24A3B	B62-710			24000	27000	230/208		3/8"- 5/8"							
THE INSIDER [®] DUCTED HEAT PUMPS			—	—	FPHFD09A3A	B61-476			9000	11000	230/208	SEE AHRI DATA IN BROCHURE	1/4"-3/8"				SEE BROCHURE			
			—	—	FPHFD12A3A	B61-477			12000	12000	230/208		1/4"-3/8"							
			—	—	FPHFD18A3A	B61-478			18000	18000	230/208		1/4"-1/2"							
			—	—	FPHFD24A3A	B62-769			24000	24000	230/208		3/8"- 5/8"							

NOTE: Cassette grilles must be ordered separately: B62-158 grille for B62-707 and B62-708. B62-159 grille for B62-709, B62-710 and B62-771.
Optional wall controllers B23-286 for PREMIER single zone models, and PRO single zone and multi zone models; B23-287 for SELECT single zone models.